


Product Image



Product Dimensions



Characteristics

Nominal Voltage		12V
Nominal Capacity (20 hour rate)		170Ah
Capacity 25°C (77°F)	10 hour rate (16.18A)	161.8Ah
	5 hour rate (30.3A)	151.5Ah
	1 hour rate (112.2A)	112.2Ah
Internal Resistance	Full Charged Battery 25°C	≤2.3mΩ
Capacity affected by Temperature (10 hour)	40°C (104°F)	102%
	25°C (77°F)	100%
	0°C (32°F)	90%
	-15°C (5°F)	70%
Self-Discharge 25°C (77°F) Capacity	after 3 month storage	92%
	after 6 month storage	84%
	after 12 month storage	65%
Charge (Constant Voltage) 25°C (77°F)	Float	Initial Charging Current Less than 34A Voltage 13.6-13.8V
	Cycle	Initial Charging Current Less than 34A Voltage 14.4-14.9V

Packaging

Battery Dimensions	Length	561mm
	Width	125mm
	Height	316mm
	Total Height	316mm
Box Dimensions	Length	576mm
	Width	140mm
	Height	376mm
Quantity Per Box		1 PC per box
Net weight Per Cell		56 kg ± 400g
Net weight Per Box		56kg
Gross Weight		56.7kg

Discharge Constant Current per Cell (Amperes at 77°F 25°C)







F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	486.2	374.0	281.4	187.0	130.9	112.2	70.1	48.1	32.0	21.54	17.80	9.35
1.65V	477.4	367.2	276.3	183.6	128.5	110.2	68.9	47.2	31.5	21.15	17.48	9.18
1.70V	468.5	360.4	271.2	180.2	126.1	108.1	67.6	46.3	30.9	20.75	17.15	9.01
1.75V	459.7	353.6	266.1	176.8	123.8	106.1	66.3	45.4	30.3	20.36	16.83	8.84
1.80V	442.0	340.0	255.8	170.0	119.0	102.0	63.8	43.7	29.1	19.58	16.18	8.50

Discharge Constant Power per Cell (Watts at 77°F 25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	935.9	720.0	541.7	360.0	252.0	216.0	135.0	92.5	61.7	41.5	34.3	18.0
1.65V	918.9	706.9	531.9	353.4	247.4	212.1	132.5	90.8	60.6	40.7	33.6	17.7
1.70V	901.9	693.8	522.0	346.9	242.8	208.1	130.1	89.1	59.4	40.0	33.0	17.3
1.75V	884.9	680.7	512.2	340.3	238.2	204.2	127.6	87.5	58.3	39.2	32.4	17.0
1.80V	850.9	654.5	492.5	327.3	229.1	196.4	122.7	84.1	56.1	37.7	31.1	16.4

Note The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values. Cell and battery designs/specifications are subject to modification without notice. Contact **MCA** for the latest information.

Performance Characteristics



Battery Construction

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Si-Rubber	Copper	Fiberglass	GEL